



5300 Beethoven Street, Los Angeles, CA 90066
 TEL: (310)306-5556 • FAX: (310)821-7413
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 5302079
800 - 1000 MHz
60 WATTS
LINEAR POWER RF AMPLIFIER

**Solid State
 Band-specific High
 Power RF Amplifier**

The 5302079 is a 60 Watt band-specific amplifier that covers the 800 – 1000 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 5302079 comes with an extended multiyear warranty.

	<u>Parameter</u>	<u>Specification @ 25° C</u>
<u>Electrical</u>		
1	Frequency Range	800 – 1000 MHz
2	Output Protection	Open and Short
3	Saturated Output Power	60 Watts min
4	Power Output @ 1dB Comp.	50 Watts min
5	Small Signal Gain	+48 dB min
6	Gain Flatness	± 1.25 dB max
7	IP ₃	+54 dBm typical
8	Input VSWR	2:1 max
9	Harmonics	-20 dBc typical @ 50 Watts
10	Spurious Signals	< -60 dBc typical @ 50 Watts
11	Input/Output Impedance	50 Ohms nominal
12	DC Input Current	12 Amps max
13	DC Input	28 VDC nominal
14	RF Input	+0 dBm max
15	RF Input Signal Format	CW/AM/FM/PM/Pulse
16	Class of Operation	A/AB
<u>Mechanical</u>		
17	Dimensions	6.55" x 4" x 1.1"
18	Weight	3 lb. max
19	Connectors	SMA female
20	Grounding	Chassis
21	Cooling	Adequate Heatsink Required
<u>Environmental</u>		
22	Baseplate Temperature	0° C to +50° C
23	Operating Humidity	95% Non-condensing
24	Operating Altitude	Up to 10,000' Above Sea Level
25	Shock and Vibration	Normal Truck Transport

Specifications subject to change without notice.



Output Protection:
 Can operate into a full Open or Short, without damage, due to the use of an Internal Circulator and Load.