



5300 Beethoven Street, Los Angeles, CA 90066
 TEL: (310)306-5556 • FAX: (310)577-9887
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 5903055
.15-230 MHz
25 WATTS
LINEAR POWER RF AMPLIFIER

**Solid State
 Broadband High
 Power RF Amplifier**

The 5903055 is a 25 Watt broadband amplifier that covers the .15-230 MHz frequency range. This small and lightweight amplifier utilizes Class A linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 5903055 comes with an extended multiyear warranty.

	<u>Parameter</u>	<u>Specification @ 25° C</u>
<u>Electrical</u>		
1	Frequency Range	.15-230 MHz
2	Saturated Output Power	25 Watts typical
3	Power Output @ 1dB Comp.	15 Watts min
4	Small Signal Gain	+43 dB min
5	Gain Flatness	± 1.5 dB max
6	IP ₃	+48 dBm typical
7	Input VSWR	2:1 max
8	Harmonics	-15 dBc typical @ 15 Watts
9	Spurious Signals	< -60 dBc typical @ 15 Watts
10	Input/Output Impedance	50 Ohms nominal
11	DC Input Current	5 Amps max
12	DC Input	28 VDC nominal
13	RF Input	+1 dBm max
14	RF Input Signal Format	CW/AM/FM/PM/Pulse
15	Class of Operation	AB
<u>Mechanical</u>		
16	Dimensions (w/Heatsink)	7.3" x 5.2" x 3.5"
17	Weight (w/Heatsink)	2.55 Lbs.
18	Connectors	SMA female
19	Grounding	Chassis
20	Cooling	Adequate Airflow Required
<u>Environmental</u>		
21	Operating Temperature	0° C to +50° C
22	Operating Humidity	95% Non-condensing
23	Operating Altitude	Up to 10,000' Above Sea Level
24	Shock and Vibration	Normal Truck Transport

Specifications subject to change without notice.



FEATURES:
 Heatsink Included (Not Shown)