



5300 Beethoven Street, Los Angeles, CA 90066  
 TEL: (310)306-5556 • FAX: (310)821-7413  
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

**MODEL 5903069**  
**1.0 - 3.0 GHz**  
**8 WATTS**  
**LINEAR POWER RF AMPLIFIER**

**Solid State  
 Broadband High  
 Power RF Amplifier**

The 5903069 is an 8 Watt broadband amplifier that covers the 1.0 – 3.0 GHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3<sup>rd</sup> order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR<sub>RF</sub> amplifiers, the 5903069 comes with an extended

	Parameter	Specification @ 25° C
<b>Electrical</b>		
1	Frequency Range	1.0 – 3.0 GHz
2	Saturated Output Power	8 Watts typical
3	Power Output @ 1dB Comp.	6 Watts min
4	Small Signal Gain	+39 dB min
5	Gain Flatness	± 1.5 dB max
6	IP <sub>3</sub>	+48 dBm typical
7	Input VSWR	2:1 max
8	Harmonics	-20 dBc typical @ 6 Watts
9	Spurious Signals	< -60 dBc typical @ 6 Watts
10	Input/Output Impedance	50 Ohms nominal
11	DC Input Current	3 Amps max
12	DC Input	13 VDC nominal
13	RF Input	+10 dBm max
14	RF Input Signal Format	CW/AM/FM/PM/Pulse
15	Class of Operation	A/AB
<b>Mechanical</b>		
16	Dimensions (w/Heatsink)	8.3" x 5.2" x 3.4"
17	Weight (w/Heatsink)	4 Lbs.
18	Connectors	SMA female
19	Grounding	Chassis
20	Cooling	Adequate Airflow Required
<b>Environmental</b>		
21	Baseplate Temperature	0° C to +50° C
22	Operating Humidity	95% Non-condensing
23	Operating Altitude	Up to 10,000' Above Sea Level
24	Shock and Vibration	Normal Truck Transport

Specifications subject to change without notice.



**FEATURES:**  
 Heatsink Included (Not Shown)