

5300 Beethoven Street, Los Angeles, CA 90066 TEL: (310)306-5556 • FAX: (310)821-7413 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

## MODEL 5303176

20-1000 MHz 30 WATTS LINEAR POWER RF AMPLIFIER

## Solid State Broadband High Power RF Amplifier

The 5303176 is a 30 Watt broadband amplifier that covers the 20-1000 MHz frequency range. This small and lightweight amplifier utilizes latest generation Class A/AB linear power devices that provide an excellent 3<sup>rd</sup> order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR<sub>RF</sub> amplifiers, the 5303176 comes backed by Ophir RF's commitment to total customer satisfaction.

	Parameter	Specification @ 25° C			
	Electrical	<u>Minimum</u>	<u>Nominal</u>	<u>Maximum</u>	Unit of Measure
1	Frequency Range	20		1000	MHz
2	Output Power P <sub>SAT</sub>	25	30		Watts
3	Output Power P <sub>1dB</sub>	12	15		Watts
4	Small Signal Gain	45			dB
5	Small Signal Flatness			± 1.5	dB
6	Gain Flatness (P <sub>SAT</sub> )			<u>+</u> 1.0	dB
7	IP <sub>3</sub>		48		dBm
8	Input VSWR	2:1			Ratio
9	Harmonics @ 10 Watts		-20		dBc
10	Spurious @ 10 Watts		-60		dBc
11	Input/Output Impedance		50		Ohms
12	DC Input Current @ 30W		4	5	Amps
13	DC Input	26	28	30	Vdc
14	RF Input for Rated Power		0	+3	dBm
15	Blanking (Rise/Fall)		2.5	5	μSec
16	DC Blanking logic	<0.5 Vdc = blanked (off); Open or 3.5-5Vdc = un-blanked (on)			
17	RF Input Signal Format	CW/AM/FM/PM/Pulse			
18	Class of Operation	A/AB			
	<u>Mechanical</u>				
19	Dimensions (L x W x H)	6" x 3" x 1.1"			
20	Weight		2.0		Lbs.
21	RF Input Connector	SMA female			
22	RF output Connector	SMA Female			
23	Grounding	Chassis			
24	Cooling	Adequate Heatsink and Air flow Required			
	Environmental				
25	Operating Temperature Baseplate	0		50	°C
26	Operating Humidity, Non Condensing			95	%
27	Operating Altitude			10,000	Feet above sea level
28	MIL-STD 810G Shock and Vibration	Shock Method 514.5 Vibration Method 516.5			
Specification	ons subject to change without notice.	d			

Certified to

ISO 9001:2015 TÜVRheinland

Precisely Right.

Date:

MADE IN USA